(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



10/516548

(43) International Publication Date 18 December 2003 (18.12.2003)

PCT

(10) International Publication Number WO 03/105374 A1

(51) International Patent Classification7:

(74) Agent: STEENBEEK, Leonardus, J.; Internationaal Oc-

(21) International Application Number: PCT/IB03/02478

(22) International Filing Date: 5 June 2003 (05.06.2003)

(25) Filing Language:

English

H04B 17/00

(26) Publication Language:

English

(30) Priority Data: 02077282.8

7 June 2002 (07.06.2002)

(71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): RUITENBURG, Leonardus, J., M. [NL/NL]; c/o Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL). SENESCHAL, Francois, J. [FR/FR]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN SINDEREN, Jan [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). FORTUIN, Robbert, P. [NL/NL]; c/o Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL).


- trooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EB, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: RECEIVER SIGNAL STRENGTH INDICATION



(57) Abstract: A receiver signal strength indication circuit comprises circuitry (A1-A4) for discretely controlled amplifying an input signal, and circuitry (NF, log, ADC) coupled to an output of the amplifying circuitry (A1-A4) for furnishing a receiver signal strength indication.